

### Amendments to the Claims

1.-28. (canceled)

29. (currently amended) A method, comprising:

receiving, at a bridge device, a read request from an expansion device;

issuing a read request from the bridge device to a portion of a system memory

predetermined to have descriptor addresses associated with the read request;

receiving descriptor blocks including descriptor data at the bridge device, wherein the descriptor data includes a transmit size, a location of the transmit data, and an address of the data to be transmitted;

storing the descriptor data in a memory on the bridge;

transmitting the descriptor blocks to the expansion device;

receiving a read request from the expansion device receiving the descriptor blocks for the transmit data associated with the descriptor blocks;

searching the memory for the descriptor addresses; and

if the descriptor addresses are located in the memory on the bridge, fetching the transmit data requested and prefetching any remaining transmit data to match the transmit size.

30. (previously presented) The method of claim 29, wherein storing the descriptor data comprises storing the descriptor data in a hash table.

31. (previously presented) The method of claim 30, wherein searching the memory further comprises searching the hash table using a read request address as a key.

32. (currently amended) The method of claim 29, the method comprising prefetching the transmit data by cacheline, if the descriptor addresses are not locating in the memory.

33. (previously presented) The method of claim 29, wherein storing the descriptor data comprises:

determining that the memory is full;  
discarding an oldest descriptor in the memory; and  
storing the descriptor in the memory.

34. (currently amended) A processor having software that causes the processor to:

receive, at a bridge device, a read request from an expansion device;  
issue a read request from the bridge device to a portion of a system memory  
predetermined to have descriptor addresses associated with the read request;  
receive descriptor blocks including descriptor data at the bridge device, wherein the  
descriptor data includes a transmit size, a location of the transmit data, and an address of the data  
to be transmitted;

store the descriptor data in a memory on the bridge;  
transmit the descriptor blocks to the expansion device;  
receive a read request from the expansion device receiving the descriptor blocks for the  
transmit data associated with the descriptor blocks;

search the memory for the descriptor addresses; and  
if the descriptor addresses are located in the memory on the bridge, fetch the transmit  
data requested and prefetching any remaining transmit data to match the transmit size.

35. (previously presented) The processor of claim 34, the software causing the processor to  
store the descriptor data comprises storing the descriptor data in a hash table.

36. (previously presented) The processor of claim 34, the software causing the processor to search the memory further comprises searching the hash table using a read request address as a key.

37. (currently amended) The processor of claim 34, the software causing the processor to prefetch the transmit data by cacheline, if the descriptor addresses are not locating in the memory.

38. (currently amended) A bridge device, comprising:

a first port to allow the device to communicate with other devices on an expansion bus;

a second port to allow the device to communicate with devices on a second bus;

a memory to store data; and

a processing element to:

receive, at a bridge device, a read request from an expansion device;

issue a read request from the bridge device to a portion of a system memory

predetermined to have descriptor addresses associated with the read request;

receive descriptor blocks including descriptor data at the bridge device, wherein

the descriptor data includes a transmit size, a location of the transmit data, and an address of the data to be transmitted;

store the descriptor data in a memory on the bridge;

transmit the descriptor blocks to the expansion device;

receive a read request from the expansion device receiving the descriptor blocks

for transmit data associated with the descriptor blocks;

search the memory for the descriptor addresses; and

if the descriptor addresses are located in the memory on the bridge, fetch the transmit data requested and prefetching any remaining transmit data to match the transmit size.

39. (previously presented) The device of claim 38, the processing element to store the descriptor data comprises storing the descriptor data in a hash table.

40. (previously presented) The device of claim 38, the processing element to search the memory further comprises searching the hash table using a read request address as a key.

41. (currently amended) The device of claim 38, the processing element to prefetch the transmit data by cacheline, if the descriptor addresses are not locating in the memory.

42. (currently amended) A bridge device, comprising:

a means for allowing the device to communicate with other devices on an expansion bus;

a means for allowing the device to communicate with devices on a second bus;

a means for storing data; and

a means for:

receiving, at a bridge device, a read request from an expansion device;

issuing a read request from the bridge device to a portion of a system memory predetermined to have descriptor addresses associated with the read request;

receiving descriptor blocks including descriptor data at the bridge device, wherein the descriptor data includes a transmit size, a location of the transmit data, and an address of the data to be transmitted;

storing the descriptor data in a memory on the bridge;

transmitting the descriptor blocks to the expansion device;

receiving a read request from the expansion device receiving the descriptor blocks for data associated with the descriptor blocks;

searching the memory for the descriptor addresses; and

if the descriptor addresses are located in the memory on the bridge, fetching the transmit data requested and prefetching any remaining transmit data to match the transmit size.